

TECHNICAL DATA SHEET OF THE PRODUCT:



WB PRIMER – Hydrophobic primer

I. APLICATION:

Water-soluble preparation based on polymer resins. Perfectly strengthens the substrate and protects against moisture. Customizations in the Water Block system as a primer for waterproofing and tile adhesive. It can be used as a hydrophobizing agent. After drying creates a transparent, colorless coating with high adhesion, which is characterized by high elasticity and vapor permeability water, is non-flammable. Suitable for indoor and outdoor use.

II. PROPERTIES:

- strengthens surface-primed substrates,
- facilitates the application of subsequent layers,
- limits the absorbency of the substrate,
- improves grip,
- bindsunstable substrate

III. SUBSTRATE PREPARATION:

Surfaces primed with WBPRIMER must be dry, load-bearing and free from substances that reduce adhesion, such as: fats, bitumen, dust, etc.

IV. PRODUCT PREPARATION:

The product is ready for use immediately after opening.



WB PRIMER



V. HOW TO USE:

It can be applied with a roller or brush. The highly absorbent substrate should be painted again after the previous layer has dried. The use of the painted substrate should be started after it has completely dried, which may take up to 24 hours after application, depending on the ambient temperature.

VI. STORAGE AND TRANSPORT:

WB Primer should be stored in tightly closed packaging at a positive temperature not exceeding 25°C.

VII. ADDITIONAL INFORMATION:

Base: water dispersion of synthetic resins.

Application temperature: from +5 to +25°C.

Storage time: 12 months in original closed containers.

Packaging: small package: 21, large package: 51.

Efficiency: 0.1 to 0.5 l/m2 depending on the evenness and absorbability of the substrate.

The technical data sheet of the product is based on many years of experience and has been created with best intent in mind. It is not legally binding and shall not be perceived as an offer within the meaning of the applicable law regulation or understood as a guarantee resulting from an order or a sales contract concluded. The data sheet contains specific, limited pieces of information, with data being obvious to experts in the field being purposefully omitted. Notwithstanding the above, the Contractor shall be obliged to act in accordance with applicable regulations, standards, and guidelines, as well as with best practices followed in the field of widely understood construction. When a new version of this technical data sheet is issued, the previous one shall no longer be considered valid.

Updated on: 12.09.2018

